



093487

1.6 MIL MACHINE LENGTH HOT MELT

Specifications and packaging

Width	48 mm
Lenght	914 m
Tape thickness	43 µm
Backing thickness	25 µm
Glue	Hot melt glue
UPC	067049791023
Case	6

Inspection

ITEMS	TEST METHOD	TESTING
Heal resistance, Steel ball (N/25mm)	GB4852	13-18
Holding power (H)	GB/T4851	≥76
Peel adhesion (H/2.5cm)	GB/T2792	15-20
Elongation (%)	GB/T7125	120-180%
Tensile strength (N/cm)	GB/T7130	≥30

Features

Environmental protection: adopt new coating production line, special glue, and new production process to achieve non-toxic and environmental protection requirements.

Good adhesion: all technical indexes are far better than ordinary adhesive tape, including the holding power and peel adhesion are 3 times of ordinary adhesive tape.

Low temperature resistance: -30°C can still be used normally.

125 Madill Blvd.
Mississauga, ON, L5W 0H1

© 2024 Imperial Dade Canada Inc. All rights reserved. PUR Value and the PUR Value logo are registered trademarks of Imperial Dade Canada Inc. The information herein is true and accurate, to the best of our knowledge. Since environmental conditions are beyond our control, no warranty, expressed or implied, is made for this product when used in a manner inconsistent with this information.