293004, 293005, 293006

Victoria Bay 1.6 Mil Machine Length Hot Melt

DESCRIPTION

General purpose biaxially-oriented polypropylene (BOPP) film carton sealing tape with specially designed pressure sensitive hot melt adhesive and unique cast film construction.

Excellent processing performance whether manually or automatically applied. Superior adhesion properties, holding force, tensile strength, and easy unwind ensure consistent, reliable seals to a variety of corrugated and linerboard boxes.

PRODUCT APPLICATION

For light to medium weight, automatic box sealing applications.

GOVERNMENT COMPLIANCE

Complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, Par. 175.105 (covers the use of pressure-sensitive adhesives and tapes for 'indirect contact' food packaging, such as box sealing). CID A-A-1684B.

Victoria Bay

125 Madill Blvd. Mississauga, ON, L5W 0H1, Canada

© 2022 Imperial Dade Canada. All rights reserved. Victoria Bay is a registered trademark of Imperial Bag & Paper. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. This data should not be considered specification.

BACKING (Cast Film) 1.0 mil (0.025 mm)

ADHESIVE Synthetic Rubber/Resin

TENSILE STRENGTH

(lb/in of width) 19 (333 N/100 mm)

ASTM 03759

ELONGATION (% at break) 125

ASTM 03759

ADHESION TO STEEL

(oz/in of width) 32 (35 N/100mm)

ASTM 03330

SHEAR TO LINERBOARD

(1/2" x 1/2" x 1000 grams) 5000+ minutes

ASTM 03654

TOTAL THICKNESS 1.60 mil (0.041 mm)

ASTM 03652

OPERATING

TEMPERATURE RANGE Application

+45°F to +120°F

(+7°C - +49°C)

Operating -10°F to 140°F (-23°C - +60°C)

COLOUR Clear

07/22 VBHotMelMac1.6TDS

